



Undersink line **H2ONDA SLIM**

THE IDEAL SOLUTION TO MEET EVERY NEED, EVEN
IN THE DOMESTIC SETTING: ENJOY MICROFILTERED,
CHILLED WATER AT HOME.

UNDERSINK WATERCOOLER

H2ONDA
Slim



The built-in solution that frees up countertop space, complemented by a wide range of manual-action columns that complete the product.

Available color combinations



Dispenser	Production of cooled water	Cooling	Capacity of the storage tank	Compressor power	Carbonator power	Power of the carbonator device	Weight	Sizes (LxPxH)*
 Slim Plus	15 l/h	Storage tank	1,6 l	1/20 Hp	100 l/h	0,8 l	16 kg	20x26,5x44 cm
 Slim Natural	15 l/h	Storage tank	1,6 l	1/20 Hp	Not present	-	14 kg	20x26,5x44 cm

OTHER TECHNICAL FEATURES

- Body material: Painted sheet metal
- Water supply pressure: 2- 3,5 bar
- Operating ambient temperature: 10 - 35° C
- Water supply temperature (min-max): 10-25° C
- Power supply: 220 V- 50 Hz monophasic
- Voltage: 230V - 50Hz
- Power consumption: 130W



USABLE WITH REFINER
REFINER 250 • 350 • 500



USABLE ONLY WITH
DRINKING WATER



R600
NATURAL REFRIGERANT GAS

Vertical operation. MAX inlet temperature: 35°C. MAX operating pressure: 3,5 bar

NOTE: this equipment requires regular maintenance periodically to ensure the requirements of potability of the drinking water treated and maintenance improvements as declared by the producer. Do not use with microbiologically dangerous water. After long periods of inactivity (3/4 week) to keep it carefully sanitizing or provide for the replacement of the filter.