

italbedis®
WATER, NATURALLY. SINCE 1989.



Domestic Line **H2ONDA SLIM**

THE IDEAL SOLUTION TO MEET EVERY NEED EVEN
IN THE HOME ENVIRONMENT:
THE PLEASURE OF COLD, MICROFILTERED WATER
EVEN AT HOME.

UPPERCOUNTER WATERCOOLER

H2ONDA

Slim



From the combination of elegance and quality comes H2Onda Slim, a dispenser with small dimensions and modern design that blends perfectly with the décor of any home.

As standard, it is equipped with an anti-flooding system and the UV LED Spider bactericidal system.



Colors combinations available



Dispenser	Production of cooled water	Cooling	Capacity of the storage tank	Compressor power	Carbonator power	Power of the carbonator device	Weight	Sizes (LxPxH)*
 H2Onda Slim Plus	15 l/h	Storage tank	1,6 l	1/20 Hp	100 l/h	0,8 l	16 kg	20x39x44 cm
 H2Onda Slim Natural	15 l/h	Storage tank	2,5 l	1/20 Hp	Not present	-	13 kg	20x39x44 cm

*drip tray included

OTHER TECHNICAL FEATURES

- Body material: **painted sheet metal**
- Water supply pressure: **2- 3.5 bar**
- Ambient operating temperature: **10 - 35° C**
- Water supply temperature (min-max): **10 - 25° C**
- Power supply: **220 V- 50 Hz single-phase**
- On/off switch - **present only in the natural version**
- Power consumption: **130 W / 80 W**



USABLE WITH:
REFINER 250 • 350 • 500



USABLE ONLY WITH
DRINKING WATER



R600
NATURAL REFRIGERANT GAS

Vertical operation. **MAX inlet temperature: 35°C. MAX operating pressure: 3,5 bar**

NOTE: this equipment requires regular maintenance periodically to ensure the requirements of potability of the drinking water treated and maintenance improvements as declared by the producer. Do not use with microbiologically dangerous water. After long periods of inactivity (3 / 4 week) to keep it carefully sanitizing or provide for the replacement of the filter.