

italbedis®

WATER, NATURALLY. SINCE 1989.



Undersink line **H2ONDA**

ITALBEDIS OFFERS A WIDE RANGE OF DISPENSERS, INCLUDING UNDER-COUNTER VERSIONS. EASY TO INSTALL, THEY ARE THE IDEAL CHOICE FOR OPTIMIZING SPACE WHILE ENSURING CONSISTENT QUALITY AND RELIABILITY.

UNDERSINK WATERCOOLER

H2ONDA



The built-in solution that allows you to keep countertops free, complemented by a wide range of manual-action columns that complete the product.

Available color combinations



Dispenser	Production of cooled water	Cooling	Capacity of the storage tank	Compressor power	Carbonator power	Power of the carbonator device	Weight	Sizes (LxPxH)*
 H2Onda Plus	15 l/h	Storage tank	1,6 l	1/20 Hp	100 l/h	0,8 l	21 kg	28x34,5x41 cm

OTHER TECHNICAL FEATURES

- Body material: **Painted sheet metal**
- Water supply pressure: **2- 3,5 bar**
- Operating ambient temperature: **10 - 35° C**
- Water supply temperature (min-max): **10-25° C**
- Power supply: **220 V- 50 Hz monophase**
- Voltage: **230V - 50Hz**
- Power consumption: **250W/ 80 W**



USABLE WITH REFINER
REFINER 250 • 350 • 500



USABLE ONLY WITH
DRINKING WATER



R600
NATURAL REFRIGERANT GAS

Vertical operation. **MAX inlet temperature: 35°C. MAX operating pressure: 3,5 bar**

NOTE: this equipment requires regular maintenance periodically to ensure the requirements of potability of the drinking water treated and maintenance improvements as declared by the producer. Do not use with microbiologically dangerous water. After long periods of inactivity (3/4 week) to keep it carefully sanitizing or provide for the replacement of the filter.