



Professional line **EUROS 80**

IDEAL FOR THOSE WHO DESIRE **COMFORT AND CONVENIENCE IN THE HO.RE.CA. INDUSTRY.**
THE BEST SOLUTION FOR THE DEMAND OF
LARGE QUANTITIES OF WATER, USING ICE BANK
TECHNOLOGY

UPPERCOUNTER WATERCOOLER

EUROS 80

mechanical version



The water supply, in the two refrigerated modes (smooth-sparkling) and ambient, takes place through practical mechanical taps.

Quick and easy installation thanks to the positioning of all water and electrical connections in the back of the dispenser. Specifically: ice bank filling tank connection, ice bank water level indicator, water supply connection, CO2 supply connection and electricity network connection.



Colors combinations available



Dispenser	Production of cooled water	Cooling	Ice bank capacity	Compressor power	Carbonator power	Power of the carbonator device	Weight	Sizes (LxPxH)*
 Euros 80	80 l/h	ice bank	8 kg	1/6 Hp	150 l/h	1,5 l	30 kg	32x67x56 cm
 Euros 80 Natural	80 l/h	ice bank	8 kg	1/6 Hp	Not present	-	28 kg	32x67x56 cm

*drip tray included

OTHERS TECHNICAL FEATURES

- Body material: **Inox Aisi 430**
- Water supply pressure: **2- 3.5 bar**
- Ambient operating temperature: **10 - 35° C**
- Water supply temperature (min-max): **10 - 25° C**
- Power supply: **220 V- 50 Hz single-phase**
- Cold water temperature (min-max): **5 - 13° C**

*Test condition: water in 20 °C - amb. temperature 25 °C

- Ice bank tank: **13.5 L**
- Power consumption: **400 W / 350 W**



USABLE WITH REFINER
REFINER 250 • 350 • 500



USABLE ONLY WITH
DRINKING WATER



R290
NATURAL REFRIGERANT GAS

Vertical operation. **MAX inlet temperature:** 35°C. **MAX operating pressure:** 3.5 bar

NOTE: this equipment requires regular maintenance periodically to ensure the requirements of potability of the drinking water treated and maintenance improvements as declared by the producer. Do not use with microbiologically dangerous water. After long periods of inactivity (3/4 week) to keep it carefully sanitizing or provide for the replacement of the filter.